dyson airblade V

HU 02 Low Voltage

Electrical

Input voltage/Frequency: 120-127 V 50&60 Hz

Standby power consumption: Less then 0.5 W

Motor specification: 1,000 W digital brushless motor

Heater type: None

Construction

Fascia: Polycarbonate

Antibacterial coating type:
HU02 (Sprayed Nickel) contains antibacterial additive in paint.
HU02 (White) contains antibacterial moulded additive.
Can help prevent the growth of bacteria.

Back plate mounting bracket: ABS/PBT Plastic

Exterior screw type: Anti-tamper 4 mm Pin-Hex

Water ingress protection to IP24

Filter

HEPA filter (Glass fibre and fleece prelayer)

99.97% of particles captured to the size of 0.3 microns

Operation

Touch free capacitive sensor activation

Hand dry time measurement: 12 seconds
(Measurement based on NSF Protocol P.335)

Sound power level: 79 dB(A)

Sound pressure level @ 2 m: 63 dB(A)[1]

Operation lock-out period: 30 seconds

Airspeed at aperture: 690 km/h / 430 mph

Maximum altitude: 2,000 metres / 6,561 ft.

Operating temperature range: 0°C-40°C / 32°F-104°F

Logistics

Single unit order code:
Sprayed Nickel 307174-01, White 307173-01

Unit barcode:
Sprayed Nickel 885609009933, White 885609009896

Net weight: 2.9 kg / 6.17 lbs

Packaged weight: 4.0 kg / 8.81 lbs

Packaged dimensions:
(H) 14.6 cm × (W) 45.4 cm × (D) 27.3 cm / (H) 5 3/4" × (W) 17 7/8" × (D) 10 3/4"

Standard warranty

5 year parts, 1 year labour

[1]Sound pressure measured at 2 m distance, in a semi-anechoic chamber.



Product range

Sprayed Nickel



White



CARBON TRUST REDUCING CO2

NSF TESTED. CERTIFIED. HYGIENIC

QUIET MARK

The Carbon label is a trademark of the Carbon Trust.
The NSF logo is the registered trademark of NSF International.
Quiet Mark is a registered trademark of the Noise Abatement Society.

For further information please contact Dyson.
1-877-397-6622
www.dysonairblade.ca


dyson airblade V

TECHNICAL SPECIFICATION




HU 02 Low Voltage

REAR ELEVATION



SIDE ELEVATION



All dimensions shown in centimeters (+/- 0.5 centimeters) (+/- 3/16")

FLOOR

Recommended installation heights from floor						
Male	X	132 cm (52 1/8")	Y	130 cm (51 3/16")	Z	93 cm (36 5/8")
Female	X	129 cm (50 3/4")	Y	126.5 cm (49 13/16")	Z	89.5 cm (35 1/4")
Child or disabled	X	107.5 cm (42 5/16")	Y	105 cm (41 3/8")	Z	65.5 cm (26 13/16")
Child 5-8	X	95.2 cm (37 1/2")	Y	92.5 cm (36 7/16")	Z	55.8 cm (22")
Child 8-11	X	105.2 cm (41 7/16")	Y	102.8 cm (40 1/2")	Z	65.8 cm (25 15/16")
Child 11-14	X	113.3 cm (44 5/8")	Y	110.8 cm (43 5/8")	Z	73.6 cm (29")

Machine dimensions			
Height 39.3 cm (15 1/2")	Width 23.4 cm (9 7/32")	Depth 10 cm (4")	

Minimum clearance
20.5 cm (8 11/16") clearance either side and 2 cm (1 3/16") above machine.

Cable entry point from floor	
Male	108.9 cm (42 7/8")
Female	105.4 cm (41 1/2")
Child or disabled	84.1 cm (33 2/16")
Child 5-8	71.7 cm (28 1/4")
Child 8-11	81.7 cm (32 3/16")
Child 11-14	89.5 cm (35 1/4")

For further information please contact Dyson.
1-877-397-6622
www.dysonairblade.ca