



# Specification Information

**Product Code:** 1144-503



**Product Name:** Shower Curtain 70"x72"

**Individual Carton UPC:** 624622114435

**Individual Carton Shipping Dimensions:** 30.5cm L x 30.5cm W x 5.1cm H (12" L x 12" W x 2" H)

**Individual Carton Shipping Weight:** 0.45kg (1.0 lbs)

**Site Location:** Frost's 1144-503 shower curtains are often specified and designed for use in both commercial and residential settings. Typically, these are used with Frost shower rods in schools/universities, recreation centres, hospitals, fitness facilities, and long-term care homes.



3D view  
Code 1144-503

## Features:

- Easy to install and maintain
- Mildew proof and cold crack (-15 degrees C) treated
- 71.25"W x 72"H
- Shower ring grommets are reinforced with aluminum
- Shower curtain hooks are sold separately

## Materials:

- 100% non-toxic PEVA and are cold crack and mildew treated. Colour is off white.

## Product Dimensions:

- 181.0cm L x 0.3cm D x 182.9cm H (71.25" L x 0.12" D x 72" H)

## Product Weight:

- 0.45 kg (1.0 lbs)

**Installation Guidelines:** Unsnap the hook and place around shower rod. Slide the shower curtain grommet within the hook and snap the hook closed. Repeat for each of the 12 hooks. Shower curtain rod and hooks sold separately.

**Maintenance:** Normal preventative maintenance and cleaning will keep Frost products functioning properly and may extend normal product life. Products should be wiped down with a damp soft cloth periodically. Approved stainless steel cleaner may be used to clean scuffs or fingerprints on stainless surfaces. Do not use harsh detergents or chemical cleaners. For general dirt and blemishes on painted steel or plastic use warm water and mild soap, or a general mild

Frost Products Ltd

5276 John Lucas Drive  
Burlington, ON, Canada, L7L5Z9

(905) 332-5700  
1-800 667-5094

info@frostproductsltd.com  
www.frostproductsltd.com



## *Specification Information*

cleaning solution. When using any type of cleaning solution, spray onto a discrete area to test before full usage. After the cleaning agent is applied, wipe off with a clean soft cloth or sponge.

**Warranty:** If any product or part proves to be defective within 12 months from date of shipment from the factory it will be repaired or replaced without any charge including freight costs when authorized. Costs resulting from the installation or removal of defective products are not covered under this warranty. Discolouration to stainless steel parts resulting from exposure to harsh environmental and / or chemicals are not considered to be defects in workmanship or material and are not covered under warranty.