



# Specification Information

**Product Code:** 714-P


**Product Name:** Automatic Liquid Soap/Sanitizer Dispenser

**Individual Carton UPC:** 624622714000

**Individual Carton Shipping Dimensions:** 15.2cm H x 30.5cm W x 15.2cm D (6" H x 12" W x 6" D)

**Individual Carton Shipping Weight:** 0.8 kg (1.75 lbs)

**Site Location:** Frost's 714-P automatic vertically mounted liquid or gel soap/sanitizer dispenser offers a practical solution for high volume areas requiring hands-free operation. Typically, the dispenser is used in schools/universities, airports, hospitals, restaurants, malls, office buildings, fitness facilities, daycares, and recreation centres. This product will quietly and automatically dispense liquid soap/sanitizer or gel sanitizer when a hand is placed within 6cm (2 ¼") from the sensor.



## Features:

- Can be wall, mirror, or stand mounted
- Non-proprietary dispenser which can lead to cost savings for end users and property managers
- Bulk filled refillable soap/sanitizer reservoir
- Powered by 3 "C" alkaline batteries (not included)
- Battery life is 1 year or 10,000 uses
- Durable plastic moulded cover
- Low battery indicator light
- Lockable
- Easy to clean and maintain

**Dispensing:** 1 cc of soap/sanitizer is dispensed when hand is placed within 6cm (2 ¼") under the unit. Bulk fill soap viscosity range of: 2,000 – 5,000 cps, (covers most liquid/gel soap/sanitizer products).

## Capacity:

- This dispenser has a 950 ml (32.1 US fl oz) capacity

## Materials:

- Body: high quality, durable, ABS white plastic

Frost Products Ltd

5276 John Lucas Drive  
Burlington, ON, Canada, L7L5Z9

(905) 332-5700  
1-800 667-5094

info@frostproductsltd.com  
www.frostproductsltd.com



## *Specification Information*

- Valve: alcohol and corrosion resistant silicone

### **Product Dimensions:**

- 26.4cm H x 11.2cm W x 10.8cm D (10.4" H x 4.4" W x 4.25" D)

### **Product Weight:**

- 0.7 kg (1.5 lbs)

**Installation Guidelines:** For unrestricted access, bottom of unit to floor should not exceed 111.7 cm (44"). Ensure touchless unit is mounted 20 cm (7.9") above any horizontal surface (30 cm / 11.8" for stainless steel). Prior to mounting using self adhesive: clean glass surface, mark clearly with removable marker or masking tape the exact location and plumb line for unit. The foam tape backing on the dispenser does not allow for repositioning of unit if it is mounted crooked or askew. Allow tape to set ten hours prior to filling dispenser with soap and loading batteries.

**Maintenance:** Normal preventative maintenance and cleaning will keep Frost products functioning properly and may extend normal product life. We recommend that units be periodically rinsed out with warm water to prevent soap build up that may hinder the performance of the valve. Products should be wiped down with a damp soft cloth periodically.

**Warranty:** If any product or part proves to be defective within 12 months from date of shipment from the factory it will be repaired or replaced without any charge including freight costs when authorized. Costs resulting from the installation or removal of defective products are not covered under this warranty. Discolouration to stainless steel parts resulting from exposure to harsh environmental and / or chemicals are not considered to be defects in workmanship or material and are not covered under warranty.